


Safety tools



# INFO

## Screwdriver range

## Industrial quality

Screwdriver range according to the new VDE Norm 1000 V IEC 60900:2004. All blades are made of high quality Molybdenum vanadium steel, black, red-covered, Polypropylen moulded. This ergonomic moulded 2-component handles from PP/TPE material guarantees a high security with normal power transmission. Every screwdriver is individually tested and marked according to the new VDE-Norm.

**1** Homogeneous sizes-adaptation of the screwdrivers haft for better power transmission. Increase of the soft area for stronger grip

**2** Exclusive, ergonomic design, non-slipping 2-component handles from PP/TPE material

**3** Roll repressive

**4** Injected blades profile on the top of the handle – for a fast access in the tool box, abrasion is not possible

**5** with 1000 V marking injected

**6** magnetic blade

An extra sliding protection of the Phillips profiles prohibits sliding out of the screw head

1000V IEC 60900:2004 GS

## VDE 2-component screwdriver with PZ slot profile



### Specifications and advantages of the PZ/FL profile.

The PZ/FL profile can only be used for combination screws that were previously screwed with a slot or recessed head PZ type screwdriver. **The screws have an inner PZ profile with an additional cross slot that also allows it to be screwed with a slot screwdriver.**



### Area of application for PZ/FL profile

The screws are mainly used in electrical installation in automatic circuit breakers and safety switches



1000 V IEC 60900:2004



Art. No.	size	total length	Ø mm	weight	PU
10 18 70	1	205	5,0 x 80	65	12
10 18 72	2	270	6,0 x 100	105	12

## 2-component VDE electricians' screwdrivers



with 2 component handle made from PP/TPE material, blade made from molybdenum vanadium steel, hardened, blasted, routine checked, insulated



▲ 1000 V IEC 60900:2004



Art. No.	lob	SB	length	weight	PU
10 19 10	75	2,5	155	25	12
10 19 12	100	3,0	185	30	12
10 19 14	100	3,5	185	30	12
10 19 16	100	4,0	195	50	12
10 19 18	125	5,5	230	75	12
10 19 20	150	6,5	255	100	12
10 19 22	175	8,0	295	180	12
10 19 24	200	10,0	320	270	12

## 2-component VDE cross slotted screwdrivers Phillips



with 2 component handle made from PP/TPE material, blade made from molybdenum vanadium steel, hardened, blasted, routine checked, insulated



▲ 1000 V IEC 60900:2004



Art. No.	size	lob	length	weight	PU
10 19 40	0	60	145	55	12
10 19 42	1	80	175	65	12
10 19 44	2	100	205	105	12
10 19 46	3	150	270	165	12

## 2-component VDE cross slotted screwdrivers Pozidriv



with 2 component handle made from PP/TPE material, blade made from molybdenum vanadium steel, hardened, blasted, routine checked, insulated



▲ 1000 V IEC 60900:2004



Art. No.	size	lob	length	weight	PU
10 19 50	0	60	135	55	12
10 19 52	1	80	175	65	12
10 19 54	2	100	205	105	12
10 19 56	3	150	270	165	12

## 2-component VDE screwdrivers Tx



with security pin, with 2 component handle made from PP/TPE material, blade made from molybdenum vanadium steel, hardened, blasted, routine checked, insulated



▲ 1000 V IEC 60900:2004



Art. No.	size	lob	length	weight	PU
10 18 50	Tx 08	100 x 3	185	70	12
10 18 52	Tx 09	100 x 3	185	70	12
10 18 54	Tx 10	100 x 3	195	75	12
10 18 56	Tx 15	100 x 3,5	195	75	12
10 18 58	Tx 20	100 x 4	195	75	12
10 18 60	Tx 25	125 x 4,5	220	85	12
10 18 62	Tx 27	125 x 5,5	230	90	12
10 18 64	Tx 30	150 x 6,5	255	100	12
10 18 66	Tx 40	175 x 8	295	120	12

## 2-component VDE screwdrivers set



with 2 component handle made from PP/TPE material, blade made from molybdenum vanadium steel, hardened, blasted, routine checked, insulated, 6-pieces. Content:

VDE Electricians' screwdriver 2,5 x 75 mm, 4 x 100 mm, 5,5 x 125 mm, 6,5 x 150 mm, VDE cross slotted screwdrivers **Phillips** or **Pozidriv** size 1 and 2



▲ 1000 V IEC 60900:2004



Art. No.	set	weight	PU
10 19 99	Phillips 6-pieces	550	1
10 19 99/PZ	Pozidriv 6-pieces	550	1

## Socket wrenches

### 2-component VDE socket wrenches DIN 7445



with 2 component handle made from PP/TPE material, blade made from molybdenum vanadium steel, hardened, blasted, routine checked, insulated



▲ 1000 V IEC 60900:2004



Art. No.	size	lob	length	weight	PU
10 25 20	4	125	220	76	6
10 25 22	5	125	220	77	6
10 25 24	5,5	125	220	76	6
10 25 26	6	125	220	79	6
10 25 28	7	125	230	112	6
10 25 30	8	125	230	144	6
10 25 32	9	125	230	116	6
10 25 34	10	125	230	118	6
10 25 36	11	125	245	175	6
10 25 38	12	125	245	178	6
10 25 40	13	125	245	188	6
10 25 44	17	125	245	237	6

### 2-component VDE socket wrenches set DIN 7445



with 2 component handle made from PP/TPE material, blade made from molybdenum vanadium steel, hardened, blasted, routine checked, insulated.

Contents: 1 piece each 5 - 5,5 - 7 - 8 - 10 - 11 - 13 mm



▲ 1000 V IEC 60900:2004



Art. No.	set	weight	PU
10 25 12	7-pieces	910	1

**haupa**

...convincing solutions