

Lock-out Systems

Nominal voltages up to 1000 V

PROTECTIVE AND AUXILIARY EQUIPMENT

VBG 125 and DIN 40008

- For indoor installations
- Protection against reconnection
- Symbol "Nicht schalten" [Do not close the circuit] acc. to national regulations (VBG 125)
- Insulating plug for screw insert
- Insulating blade for NH fuse holders
- Lock-out systems for circuit breakers



Lock-out system with 3 modules (mods.)



Type	Size	Dimensions	Part No.
A Insulating Plug For screw insert			
SE E14	E14	Ø20 x 40 mm	785 639
SE E18	E18	Ø25 x 40 mm	785 650
SE E27 E33	E27 and 33	Ø45 x 55 mm	785 640
B Insulating Blade For NH fuse holders and distribution blocks			
SE NH00	00	80 mm	785 641
SE NH0	0	125 mm	785 642
SE NH1	1	135 mm	785 643
SE NH2 3	2 and 3	150 mm	785 644
C Lock-out System For single-pole and multi-pole circuit breakers with a clamping range of 45 mm			
SE REG 1TE	1 mod.	52 x 17 mm	785 638
SE REG 2TE	2 mods.	52 x 34 mm	785 652
SE REG 3TE	3 mods.	52 x 51 mm	785 637